

### Amendments to the Specification

Please replace paragraph 21 of the specification with the following paragraph:

A1  
“[0023] FIG. 2A is an exploded perspective view of the wireless communication device 100 shown with respect to FIG. 1, where internal components of the wireless communication device 100 are more clearly shown. As may be seen with respect to the Figure 2A, the wireless communication device 100 includes a top housing 104 having catches 106, catch buttons 106a and an LED port 108. The catches 106 hold the handheld device 101 as the handheld device 101 inserts into the wireless communication device 100.”

Please replace paragraph 30 of the specification with the following paragraph:

A2  
“[0032] In addition to the pass-through serial connector 116, the wireless communication device 100 includes a clip assembly 118. The clip assembly 118 couples with the top housing 104, as shown with reference to the Figure 2A. The top housing 104 couples with the clip assembly 118 using any suitable technique, such as fasteners, rivets, or the like. The clip assembly 118 holds the handheld device 101 with the wireless communication device 100 using clips 118a. The configuration of the clips 118a allow holding of the handheld device 101 by the wireless communication device 100 as shown with reference to the Figure. Therefore, the top housing 104 and the clips 118a provide a mechanical interface between the wireless communication device 100 and the handheld device 101. The wireless communication device 100 also includes the battery 126 which provides power to the wireless communication device 100. In one embodiment of the present invention, the battery 126 is preferably a 3.6 V lithium-ion battery providing between about 1130 mA to about 1500 mA of power.”